

BWS 30



- LED Schienenstrahler
- Gehäuse aus lackiertem Alu-Druckguss, klares Schutzglas
- COB-LED-Modul in 4 Ausstrahlwinkeln 15°/24°/40°/60°
- Eutrac®-3-Phasen-Adapter
- 4 Standard Gehäusefarbenkombinationen (andere Farbkombinationen auf Anfrage)
- Schutzart: IP20
- Schutzklasse: I
- Integriertes elektronisches Versorgungsteil (Standard: 30.000h / 50.000h auf Anfrage)
- CRI >90
- Dimmbare Ausführung verfügbar (DALI)

Auf Anfrage

- Dimmbare Version
- Anbaumontage mit Deckenrosette
- Einhängestrahler für Rasterdecken
- Für Lebensmittel (Gemüse-, Back- und Fleischware) optimierte Versionen
- CRI >80

- Stromschienen siehe ab Seite 34

- LED power-track-light
- Body in coated die-cast aluminium, clear glass
- COB-LED-module with optics in 15°/24°/40°/60°
- Eutrac®-3-phase-adapter
- 4 standard housing colours combination (other colour combinations on request)
- Protection Rating: IP20
- Protection Class: I
- Built in electronic power supply (standard 30.000h / 50.000h on request)
- CRI >90
- Dimmable variation available (DALI)


On request

- Dimmable version
- Surface mounted with ceiling rose
- Spotlight to hang in grid ceilings
- Optimized versions for groceries (vegetables, bakery and meat products)
- CRI >80


- Power-tracks see from page 34







BWS LED Schienenstrahler | LED power-track-light
26 W / 220÷240V / CRI>90



⚙️ 15°	○	●	●○	●	26 W
4000 K	BWS-30NW11-1S	BWS-30NW12S	BWS-30NW12/1S	BWS-30NW17-7S	2418 lm
3500 K	BWS-30WNW11-1S	BWS-30WNW12S	BWS-30WNW12/1S	BWS-30WNW17-7S	2417 lm
3000 K	BWS-30WW11-1S	BWS-30WW12S	BWS-30WW12/1S	BWS-30WW17-7S	2382 lm
2700 K	BWS-30SW11-1S	BWS-30SW12S	BWS-30SW12/1S	BWS-30SW17-7S	2290 lm
⚙️ 24°					
4000 K	BWS-30NW11-1	BWS-30NW12	BWS-30NW12/1	BWS-30NW17-7	2403 lm
3500 K	BWS-30WNW11-1	BWS-30WNW12	BWS-30WNW12/1	BWS-30WNW17-7	2401 lm
3000 K	BWS-30WW11-1	BWS-30WW12	BWS-30WW12/1	BWS-30WW17-7	2367 lm
2700 K	BWS-30SW11-1	BWS-30SW12	BWS-30SW12/1	BWS-30SW17-7	2276 lm
⚙️ 40°					
4000 K	BWS-30NW11-1F	BWS-30NW12F	BWS-30NW12/1F	BWS-30NW17-7F	2473 lm
3500 K	BWS-30WNW11-1F	BWS-30WNW12F	BWS-30WNW12/1F	BWS-30WNW17-7F	2471 lm
3000 K	BWS-30WW11-1F	BWS-30WW12F	BWS-30WW12/1F	BWS-30WW17-7F	2436 lm
2700 K	BWS-30SW11-1F	BWS-30SW12F	BWS-30SW12/1F	BWS-30SW17-7F	2342 lm
⚙️ 60°					
4000 K	BWS-30NW11-1-60	BWS-30NW12-60	BWS-30NW12/1-60	BWS-30NW17-7-60	2445 lm
3500 K	BWS-30WNW11-1-60	BWS-30WNW12-60	BWS-30WNW12/1-60	BWS-30WNW17-7-60	2443 lm
3000 K	BWS-30WW11-1-60	BWS-30WW12-60	BWS-30WW12/1-60	BWS-30WW17-7-60	2408 lm
2700 K	BWS-30SW11-1-60	BWS-30SW12-60	BWS-30SW12/1-60	BWS-30SW17-7-60	2315 lm



○ Weiß | White
●○ Schwarz/Weiß | Black/White
● Schwarz | Black
● Alugrau | Aluminium





Blankensteinstraße 34-36

32257 Bünde

Tel. 0 52 23 / 18 35 70

Fax 0 52 23 / 57 23

info@storelights.de

www.storelights.de

**Ein Service von
Storelights.de
-Ihre helle Freude-**